

# ReddiSpace

Acoustic Booths



View AR and 3D visual tools, statement of line, and more at:  
**FRIANT.COM**

**FRIANT**





**FRÍANT**





ReddiSpace **QuickTime**





ReddiSpace **QuickTime**





ReddiSpace **MeTime**





ReddiSpace **MeTime**





ReddiSpace **WeTime**





ReddiSpace **OurTime**





ReddiSpace









ReddiSpace





ReddiSpace





Introducing ReddiSpace, the ultimate solution for a private and focused environment. Our premium acoustic booth combines functionality and style for the ultimate productive workspace. For moments when you need a quiet space to concentrate and minimize distractions, **ReddiSpace is ready.**

### Soundproofing

Designed with exceptional soundproofing performance, providing a private and distraction-free environment that allows you to focus, communicate, and work without interruptions from external noise.



### Adaptability

Equipped with a convenient work surface, lighting, and plug-and-play power, ReddiSpace supports your work style and needs. Its casters make the booth mobile, allowing you to easily move and place it in different locations within your workspace as needed.

### Customization

From the exterior casing to the interior walls, carpet, and more, design your ideal ReddiSpace to reflect your unique style and compliment your workplace aesthetic.



### UL Certified













ReddiSpace has undergone rigorous testing and complies with industry standards. Engineered with stability and security in mind, ReddiSpace is UL certified, meeting recognized safety requirements and providing a safe and comfortable station for your workspace.








# Finishes









## Interior (Acoustical PET)

							
18 Gray	03 Lt Gray	22 Taupe	27 Sky	08 Lilac	26 Eggplant	46 Ivy	05 Lake
							
06 Tangerine	12 Avocado	15 Lime	14 Café				








## Top Finish (Worksurfaces)

			
CW White	BU Black	938 California Walnut	699 Rift




## Fabric (Sofas)

							
1333 Gray	1300 Tan	1302 Sunshine	1313 Periwinkle	1320 Mauve	1321 Sunset	1309 Moss	1228 Neptune

## Carpet

						
GR Gray	GB Gray-Blue	AS Ash	GN Green	YL Yellow	GP Graphite	CH Charcoal

## Casing

		
CW White	BU Black	8180 Oak



# Materials

## Casing

Layered composition of sheet metal, fire-rated gypsum board, recycled acoustic foam, and acoustic felt

## Glass

10mm tempered glass with aluminum frame

## Exterior

Sheet metal with solid PVC color or wood PVC color

## Frames

Aluminum

## Door

5+5mm laminated tempered glass with black painted aluminum frame

ADA door: single 10mm tempered glass with aluminum frame

## Carpet

Anti-static, stain resistant, low-loop pile carpet



# ReddiSpace Specifications



## QuickTime

**Exterior Dimensions**  
40.5" x 40.5" x 86.5"

**Power**  
(2) outlets, (1) B-A, (1) USB-C

**Ventilation**  
2 Fans  
Airflow: 1100 L/min  
Air replaced every 1.65 min

**Lighting**  
Sensor

## MeTime

**Exterior Dimensions**  
63.5" x 47" x 86.5"

**Power**  
(4) outlets, (2) USB-A, (2) USB-C

**Ventilation**  
2 Fans  
Airflow: 2930 L/min  
Air replaced every 1.0 min

**Lighting**  
Sensor

## WeTime

**Exterior Dimensions**  
86.5" x 47" x 86.5"

**Power**  
(4) outlets, (2) USB-A, (2) USB-C

**Ventilation**  
2 Fans  
Airflow: 2930 L/min  
Air replaced every 1.58 min

**Lighting**  
Sensor

## OurTime

**Exterior Dimensions**  
86.5" x 59" x 86.5"

**Power**  
(4) outlets, (2) USB-A, (2) USB-C

**Ventilation**  
4 Fans  
Airflow: 5860 L/min  
Air replaced every 1.0 min

**Lighting**  
Sensor



# ReddiSpace Specifications



UL	UL Listing	UL962
EMISSIONS	Indoor Air	ISO 16000-3:2011
FIRE RESISTANCE	Fire Resistance Testing	EN 1363-1:2020
NOISE TRANSMISSION	NIC	30dB
POWER	Infeed	Single-circuit plug-and-play 10' cord
	Interior Controls	Lights and ventilation fan are motion sensor activated
	Power	S: (2) outlets, (1) USB-A, (1) USB-C W: (4) outlets, (2) USB-A, (2) USB-C M: (4) outlets, (2) USB-A, (2) USB-C L: (4) outlets, (2) USB-A, (2) USB-C ADA: (4) outlets, (2) USB-A, (2) USB-C
	Ventilation	S (2 fans): air flow is 1100L/minute; Air replaced every 1.65 minutes. W (2 fans): air flow is 2930L/minute; Air replaced every 1.00 minute. M (2 fans) : air flow is 2930L/minute; Air replaced every 1.58 minutes. L (4 fans): air flow is 5860L/minute; Air replaced every 1.00 minutes. ADA (4 fans): air flow is 5860L/minute; Air replaced every 1.2 minutes.
	Lighting	S: LED light 7W 3000K W: LED light 7W 3000K M: LED light 7W 3000K L: LED light 7W 3000K ADA: LED light 7W 3000K
	Power Draw (while light and fans are running)	S: 11W, 2A W: 44W, 3A M: 44W, 3A L: 80W, 5A ADA: 150W, 10A
TITLE 24	Lights	Motion sensor included



CONSTRUCTION	Exterior	Sheet metal with solid or woodgrain PVC color
	Interior	9mm acoustic panel
	Front and Back	10mm safety glass with aluminum frame
	Door	5+5mm laminated tempered glass with black painted aluminum frame
DIMENSIONS	ADA Door	Single 10mm tempered glass with aluminum frame
	Exterior Dimensions	S: 40.5" W x 40.5" D x 86.5" H
		W: 63.5" W x 47" D x 86.5" H
		M: 86.5" W x 47" D x 86.5" H
		L: 86.5" W x 59" D x 86.5" H
	Interior Dimensions	ADA: 86.5" W x 63" D x 86.5" H
		S: 36" W x 36" D x 82" H
		W: 58.5" W x 42" D x 82" H
		M: 82" W x 42" D x 82" H
		L: 82" W x 54" D x 82" H
		ADA: 82" W x 57" D x 82" H







06.12.2025

**FRÍANT**

View AR and 3D visual tools, statement of line, and more at:  
**FRIANT.COM**