

REDDISPACE PRODUCT SPECIFICATIONS



UL	UL Listing	UL962
EMISSIONS	Indoor Air	ISO 16000-3:2011
FIRE RESISTANCE	Fire Resistance Testing	EN 1363-1:2020
NOISE TRANSMISSION	NIC	30dB
	Infeed	Single-circuit plug and play 10' cord
	Interior Controls	Lights and ventilation fan are motion sensor activated
	Power	S: (2) outlets, (1) USB-A, (1) USB-C W: (4) outlets, (2) USB-A, (2) USB-C M: (4) outlets, (2) USB-A, (2) USB-C L: (4) outlets, (2) USB-A, (2) USB-C ADA: (4) outlets, (2) USB-A, (2) USB-C
POWER	Fan air exchange	S (2 fans): air flow is 1100L/minute; Air Replaced every 1.65 minutes. W (2 fans): air flow is 2930L/minute; Air Replaced every 1.00 minute. M (2 fans): air flow is 2930L/minute; Air Replaced every 1.58 minutes. L (4 fans): air flow is 5860L/minute; Air Replaced every 1.00 minutes. ADA (4 fans): air flow is 5860L/minute; Air Replaced every 1.2 minutes.
	Lighting	S: LED light 7W 3000K W: LED light 7W 3000K M: LED light 7W 3000K L: LED light 7W 3000K ADA: LED light 7W 3000K
	Power Draw (while light and fans are running)	S: 11W, 2A W: 44W, 3A M: 44W, 3A L: 80W, 5A ADA: 150W, 10A
TITLE 24	Lights	Motion sensor included

CONSTRUCTION	Exterior	Sheet metal with solid or woodgrain PVC color
	Interior	9mm acoustic panel
	Front and Back	10mm safety glass, with aluminum frame
	Door	5+5 laminated tempered glass, with black painted aluminum frame ADA door: Single 10mm tempered glass with aluminum frame
DIMENSIONS	Exterior Dimensions	S: 40.5" W x 40.5" D x 86.5" H W: 63.5" W x 47" D x 86.5" H M: 86.5" W x 47" D x 86.5" H L: 86.5" W x 59" D x 86.5" H ADA: 86.5" W x 63" D x 86.5" H
	Interior Dimensions	S: 36" W x 36" D x 82" H W: 58.5" W x 42" D x 82" H M: 82" W x 42" D x 82" H L: 82" W x 54" D x 82" H ADA: 82" W x 57" D x 82" H